

**SFS intec self-closing door system
for doors: a five-star protagonist**



SFS intec has designed for you the aesthetic appearance you have always wanted for a self-closing door system.

The current SFS intec closing-door system has been developed following the aesthetics aspect of a normal hinge and in accordance to the technical requirements of architects and door producers.

The self-closing door mechanism has the same dimensions as the adjustable hinges, is easy and quick to fit, and adapts to any adjustments.

There are already numerous important/famous hotels which managed to enhance the physical aspect of their doors at their best by installing this system.

It is specifically adapted to renovations where space is limited as it is easily fitted, and helps you turn a traditional door in a self-closing one in a very simple and quick way.

- The self-closing door mechanism has the same dimensions as the adjustable hinges (15 x 92 mm).
- It is easy to fix and adjust.
- It has been tested to 100,000 cycles with doors weighing up to 60 kgs
- The finish zinc-coated 8my chromated, resists to further 280 hours in salt spray test according to the DIN 50021 standard.
- Available in Kit for "REI 30" and traditional doors.
- Several companies have had their "REI 30" doors approved with this system.



Our self-closing door system is used in:

Roma,	<i>Holiday Inn Express ★★★★★; Boscolo Grand Hotel Palace ★★★★★S.;</i>
Venezia,	<i>Hotel Bellini ★★★★★;</i>
Firenze,	<i>Hotel Marco Polo ★★★★★;</i>
Bergamo,	<i>Hotel Cappello D'oro ★★★★★;</i>
Verona,	<i>Villa Quaranta Park Hotel ★★★★★;</i>
Milano,	<i>Hotel Poliziano Fiere ★★★★★; Hotel Scià on Martin ★★★★★;</i>
Castrocaro,	<i>Grand Hotel Terme ★★★★★;</i>
Riccione,	<i>Hotel Roma ★★★★★;</i>
Napoli,	<i>Serius ★★★★★;</i>
Sorrento,	<i>Central ★★★★★;</i>
Capri,	<i>La Palma ★★★★★.</i>





SFS intec self-closing door system is also available for flush-fit doors

2 versions dedicated to flush-fit door applications have been added to the SFS intec self-closing door system range.

The first one includes the self-closing door system with the laps on both bodies.

The second one has been designed with one lap on the female and the studs on the male. This system has also been approved to 100,000 cycles with weighing up to 60 kilos.

It has the same dimensions as the 15 x 92 mm-diameter adjustable hinges and is as easy and quick to fit as the self-closing door system for rebated doors.

This system is sold in a kit including 2 adjustable hinges + 1 self-closing mechanism and the related decorative caps available in brass, nickel and matt nickel finish.



	Ø	Loading in KG	Interaxis mm.	Finish	Order code	Piece per package
Self-closing system rebuted application The box contains: - 3 hinges 11Rx92 with 60 mm studs - 1 self closing mechanism - 8 caps Door closing system tested to 100.000 cycles on door Rei 30	15	60	24	Brassed	914624 dx	
	15	60	24	Nickel	921503 dx	
	15	60	24	Matt nickel	921505 dx	
	15	60	24	Brassed	914623 sx	
	15	60	24	Nickel	921506 sx	
	15	60	24	Matt nickel	921507 sx	
The box contains: - 2 hinges 11Rx92 with 45 mm studs - 1 self closing mechanism - 6 caps	15	45	24	Brassed	952572 sx	
	15	45	24	Nickel	952569 sx	
	15	45	24	Matt nickel	952571 sx	
	15	45	24	Brassed	952575 dx	
	15	45	24	Nickel	952573 dx	
	15	45	24	Matt nickel	952574 dx	
Single-self closing mechanism	15		24	Duble zinc coat DT yellow chromated 60 mm studes	930204 dx 930202 sx	1 1
	15		24	Duble zinc coat DT yellow chromated 45 mm studes	945014 dx 945012 sx	1 1
Adjustable hinge with studs 8,7x60 mm for self closing system	15		24	Duble zinc coat DT yellow chromated 60 mm studes	914632	10
Self-closing system with two laps flush fit application The box contains: - 2 hinges 11Rx92 with laps - 1 self closing mechanism - 6 caps Door closing system tested to 100.000 cycles	15	60		Brassed	975625 sx	
				Brassed	975626 dx	
Single self-closing mechanism with two laps flush fit application	15			Brassed	974060 sx 974062 dx	
Adjustable hinge with two laps				Duble zinc coat DT yellow chromated	974064 sx 974066 dx	10 10
Single self-closing mechanism with one lap and 60 mm studs	15			Brassed	968662 sx 968663 dx	
Adjustable hinge with lap and 60 mm studs				Duble zinc coat DT yellow chromated	968666 sx 968711 dx	

SFS intec considers that all information is correct at time of publication, and reserves the right to make changes or modifications without prior notification - HT 12.00.02 GB
SFS intec cannot be held responsible for the incorrect application or adjustment of these products.